

English only/ nur Englisch/ jen anglicky

MEVI-CZ s.r.o.  
Hlavníčkovo nábřeží 5664  
760 01 Zlín  
Czech Republic



[www.mevi.cz](http://www.mevi.cz)

We produce for you on these machines.

<b>CNC-Milling</b>		
<b>HAAS UMC-750 (5-Axis)</b>		
2x	Work piece max	760x400x400
	X Axis	762 mm
	Y Axis	508 mm
	Z Axis	508 mm
	B Axis Tilt	+110° to -35°
	C Axis Rotation	360 °
	Speed range	0-12000 1/min
	Control system	HAAS
<b>ZPS - MCFV 1060 NT</b>		
1x	Work piece max	1016x610x760
	Speed range	0-8000 1/min
	Control system	Heidenhain TNC 426
<b>INTOS – FNG 40 CNC</b>		
1x	Work piece max	600x400x400
	Speed range	0-4000 1/min
	Control system	Heidenhain TNC 310
<b>MIKRON VCE500</b>		
1x	Work piece max	508x406x508
	Speed range	0-7500 1/min
	Control system	HAAS
	Full 4th axes-cnc rotary table	
<b>HAAS VF4B</b>		
1x	Work piece max	1270x508x635
	Speed range	0-7500 1/min
	Control system	HAAS
	Full 4th axes-cnc rotary table OR	
	Full 5th axes-cnc rotary table	

<b>HAAS VF2SS</b>		
3x	Work piece max	762x406x508
	Speed range	0-12000 1/min
	Control system	HAAS
	Full 4th axes-cnc rotary table	
<b>HAAS Super MiniMill 2</b>		
1x	Work piece max	508x406x355
	Speed range	0-10000 1/min
	Control system	HAAS
<b>CNC-Turning</b>		
<b>HAAS ST30SSY</b>		
1x	Spindle bore	70
	Turning diameter max	406
	Turning length max	584
	Speed range	4500 1/min
	Number of tools/driven tools	12/12
	Control system	HAAS
	Accessory	C+Y Axis
<b>ZPS - S50</b>		
1x	Spindle bore	50
	Turning diameter max	270
	Turning length max	535
	Speed range	4000 1/min
	Number of tools/driven tools	12/6
	Control system	Fanuc OT-C
<b>MAS-MT32CNC Teach-In</b>		
1x	Spindle bore	50
	Turning diameter max	150
	Turning length max	750
	Speed range	0-4000 1/min
	Control system	Heidenhain. ManualPlus 4110

<b>Milling</b>		
<b>TOS - FGS 25/32</b>	Work table	720x360x420
<b>TOS - FGS 25/32</b>	Work table	720x360x420
<b>FORTHWORTH</b>	Work table	810x300x400
<b>FORTHWORTH</b>	Work table	1100x450x400
<b>Turning</b>		
<b>TOS – SV18</b>	Spindle bore	40
	Turning diameter max	350
	Turning length max	750
<b>ZPS – SR50A</b>	Spindle bore	50
	Turning diameter max	450
	Turning length max	450
<b>TOS – SU50AT</b>	Spindle bore	50
	Turning diameter max	500
	Turning length max	1000
<b>Grinding</b>		
<b>- Surface</b>		
<b>TOS – BPH 320/1000</b>	Work place	320x1000x350
<b>- Cylindrical In/Out</b>		
<b>TOS - BU 287</b>	Outside diameter max	280
	Inside diameter max	140
	Grinding length max	600